Reply to Office Action of March 15, 2007

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A pigmented ink composition comprising a pigment, a resin

Docket No.: 0020-5330PUS1

having an acidic group and an organic solvent having a boiling point of at least 150°C which is

present in an amount of from 50 to 90% by weight based on the whole weight of the ink

composition, wherein said resin having an acidic group is a water-insoluble acrylic resin having a

hydrophobic group and an acid value of 10 to 300 mg-KOH/g, and

wherein said organic solvent is selected from the group consisting of a monoalkyl ether

monoalkyl ester derivative of (poly)alkylene glycol and a dialkyl ester derivative of (poly)alkylene

glycol.

2. (Original) The pigmented ink composition according to claim 1, which comprises 0.1 to

20% by weight of the pigment and 0.5 to 30% by weight of the resin having the acidic group based

on the whole weight of the ink composition.

3. (Cancelled)

4. (Previously Presented) The plamented ink composition according to claim 1, wherein said

resin having the acidic group has a weight average molecular weight of 1 x 104 to 3 x 105, and a

molecular weight distribution of 1.5 to 10.

5. (Previously Presented) The pigmented ink composition according to claim 1, wherein said

2

resin having the acidic group is a resin having an other bond.

JWB/enm

Application No. 10/518,452 Amendment dated June 13, 2007

Keply to Office Action of March 15, 2007

6-7, (Cancelled)

8. (Previously Presented) The pigmented ink composition according to claim 1, wherein

Docket No.: 0020-5330PUS1

said organic solvent having a boiling point of at least 150°C is a polar solvent.

9. (Previously Presented) The pigmented ink composition according to claim 1, wherein

said organic solvent having a boiling point of at least 150°C is an other solvent.

10. (Cancelled)

11. (Previously Presented) The pigmented ink composition according to claim 1, wherein

said organic solvent having a boiling point of at least 150°C is at least one compound selected

from the group consisting of ethylene glycol monoalkyl ether monoalkyl ester, diethylene glycol

monoalkyl ether monoalkyl ester, triethylene glycol monoalkyl ether monoalkyl ester, propylene

giveol monoalkyl ether monoalkyl ester, dipropylene glycol monoalkyl ether monoalkyl ester,

tripropylene glycol monoalkyl ether monoalkyl ester, ethylene glycol dialkyl ester, diethylene

giveo) dialkyl ester, triethylene glycol dialkyl ester, propylene glycol dialkyl ester, dipropylene

glycol dialkyl ester and tripropylene glycol dialkyl ester.

12. (Previously Presented) The pigmented ink composition according to claim 1, which is

used in an ink-let printer, wherein said ink composition has a surface tension of at least 25 mN/m at

3 JWB/enm

Application No. 10/518,452 Amendment dated June 15, 2007 Reply to Office Action of Murch 15, 2007

20°C and a viscosity of 2 to 30 cp at 20°C, and the pigment has a dispersion average particle size of 0.01 to 0.5 µm.

Docket No.: 0020-5330PUS1

4 JWB/enm